



Refrigerated tables



- 2-3-4 door tables in refrigerating group or prearranged models, as well as in the static, ventilated or low temperature ventilated (-20°C) operation version.

Constructive features

- Cell, feet, and external walls made entirely of stainless steel AISI 304 Cr-Ni 18/10
- One-body structure
- 50 mm insulation, in high density polyurethane foam
- Spring doors and magnetic dosing
- Internal demountable uprights and accessories
- Independent working top with or without apron (options: stainless steel, alimentary polyethylene, Sardinian granite)
- Components in conformity with all European standards

Technical features

- Extractable refrigerating group
- Easily accessible electric control panel
- Automatic hot gas circulation de-frosting system with already programmed operation cycle
- Operation through central controls on front panel

Included accessories

- 8 guide couples for pan supports for each door compartment
- (60x40) pans not included





Refrigerated tables

Technical features

Model	T°C	Power kW/h	External Size			Volume M ³
			L	cm P	H	
TFS 160/80 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	165	80	86	1,58
TFS 200/80 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	205	80	86	1,97
TFS 260/80 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	260	80	86	2,55
TFS 140/70 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	135	70	86	1,07
TFS 180/70 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	180	70	86	1,42
TFS 220/70 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	225	70	86	1,76
TFE 160/80 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	160	80	86	1,58
TFE 215/80 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	215	80	86	1,97
TFE 270/80 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	270	80	86	2,55
TFE 140/70 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	142	70	86	1,07
Tavolo TFE 180/70 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	187	70	86	1,42
TFE 230/70 Refrigerated table with upstairs h10	-2° +8°C	kW 0,75 230 V single phase	230	70	86	1,76